


X1iD UHF 18000-6C **RFID Label Printer**

Support flexible anti metal labels (thickness less than or equal to 1.5mm)



High-Performance RFID Label Printer

Intelligent and Efficient



This is a professional RFID label printer that is stable, reliable, versatile, and easy to use. It is a reliable label printing device.

Our technical team will provide professional and effective technical support, so that you have no worries.



Stable and reliable, easy to use



Supports Windows and Linux systems



Support flexible anti metal labels



Support RFID reading and writing



Fastest 6 inches/second printing



Full featured label design software

RFID(UHF) Label Printer Specifications

Model	X1iD
Printing method	Direct thermal & Thermal transfer
Resolution	300 DPI(11.8dots/mm)
Maximum print speed	6 IPS(152.4mm/s)
Maximum print width	4.15" (105.6mm)
Maximum print length	78.7"(2000mm)
Memory	8 MB Flash ROM, 16 MB SDRAM
Media	Roll-feed, die-cut, continuous, fan-fold, labels, tickets in plain paper or thermal paper Width: 4.6"(118mm) max.,0.8"(20mm)min. Supply roll: OD 5"(127mm) max., ID 1"(25.4mm) min. Thickness: 0.06~1.5mm(0.002"~0.06"), including liner, support flexible on-metal labels.
Ribbon	Wax, Wax/Resin, Resin Ribbon roll: OD 2.75"(70mm) max. with ID 1"(25.4mm) core or ID 0.5"(12.7mm) core Max width: 110mm; Max length: 300M
Media sensor	Adjustable reflective & Transmissive
RFID function	Integrated high performance RFID reader/encoder supports labels compatible with UHF EPC Gen 2/ISO 18000-6C
Bar Code Types	1D Barcode : Code 39, Code 93, Code 128, Codabar, EAN-8/13/128, Interleave 2 of 5, UCC-128, UPC A/E 2 and 5 add-on, etc. 2D Barcode : Data Matrix, MaxiCode, PDF417,QR, etc.
Interfaces	RS-232, USB, LAN
Power rating	24 VDC, 2.0 A
Weight	2.65KGS
Dimensions	W208 x D310 x H195 mm
Operation environment	Temperature: 32° F ~ +104° F (0° C ~ 40° C) Relative humidity: 5% - 85% non condensing
Storage environment	Temperature: -40° F ~ +140° F (-40° C ~ 60° C) Relative humidity: 5% - 85% non condensing
Options	External label bracket, Peeler, Bluetooth module

The above specifications and parameters are subject to the actual product.

ZMIN Technologies Co.,Ltd.

Barcode / RFID Label Printer Manufacturer

Email: support@zmin.com.cn